



BASIX VALVE TYPE T/N

ART. NO. 450144

GENERAL



The KEOFITT BASIX Sampling Valve is our CIP-able sampling valve for less demanding applications. Replaces non-hygienic sampling cocks. More than 20 different configurations available.



The sampling valve can be used for any process sampling for chemical and/or physical analysis.



Cleaning: Valve in open position: Cleanable by means of CIP using the detergent solution suitable for the actual process media. For further advice, please contact Keofitt.

Autoclavable.



Designed for sampling of liquids with a viscosity of up to approx. 100 cP containing no particles larger than Ø1.5 mm. Sampling of more viscous liquids is possible, only will it take longer (depending on process pressure).

FEATURES



Installation: Tank welding



Outlet: Hose piece



Operation: Pneumatically operated / Lever handle (#600170)



Membrane: Silicone (#400051)



Festo Fitting QSML-M5-4

Head assembly: Hand tight using a tommy bar or maximum 15 Nm. Tommy bar included (#900118).

CERTIFICATION*

- · EU EC 1935/2004 · EU EC 2023/2006 · DK No. 1248 10/2018 · 3-A Certificate · 3.1 Material Certificate
- · ATEX 2014/34/EU · PED 2014/68/EU · FDA CFR 21 §177.2600 · USP Class VI · Keofitt DoC

TECHNICAL DATA

Material (process contact)

Steel parts
 Membrane
 AISI 316L (1.4404)
 Membrane
 SILICONE, GREY (#400051)

Material (without process contact)

• Steel parts AISI 304 (1.4307) • Lever handle AISI 316L (1.4404)

Membrane

· Article SILICONE, GREY (#400051)

· Certification* · EU EC 1935/2004 · EU EC 2023/2006

 \cdot DK No. 1248 10/2018 \cdot FDA CFR 21 §177.2600 \cdot USP Class VI

 $\cdot \, \mathsf{REACH} \cdot \mathsf{RoHS} \cdot \mathsf{ADI} \, \mathsf{Free} \cdot \mathsf{Keofitt} \, \mathsf{DoC}$

Surface Treatment

 $\begin{array}{ll} \cdot \text{Outside} & \text{Ra} \leftrightharpoons 1.2 \, \mu\text{m} \\ \cdot \text{Inside (wetted surface)} & \text{Ra} \leftrightharpoons 0.8 \, \mu\text{m} \\ \cdot \text{Process connection} & \text{Ra} \leftrightharpoons 0.8 \, \mu\text{m} \end{array}$

Pressure & Temperature


Pressure 0 - 6 bar / 0 - 87 psi
 Temperature 1 - 130°C / 34 - 266°F
 Air supply 5 - 7 bar / 73 - 102 psi

Net Weight

· kg/lbs 0.526 kg/1.158 lbs

Spareparts

774501 PARTS FOR BASIX VALVE BODY 774444 PARTS FOR 4KAI/BASIX HEAD N





Ø28 mm

